

## IN THE CLAIMS

1. [currently amended] Method for monitoring of a communication link between a source network node and a destination network node, which comprising  
- employing, on said communication link, employs the IPSec protocol for tunneling P packets between the source network node and the destination network node, said method comprising at least the step of transmission of-  
- transmitting an acknowledgement packet by the destination network node if at least one of a first condition and a second condition is fulfilled, said first condition being the reception of at least a predetermined number of IPSec packets after transmission of the previous acknowledgement packet, and said second condition being the reception of an IPSec packet via the communication link after a predetermined time has passed after transmission of the previous acknowledgement packet.

2. [currently amended] ~~A method according to claim 1~~ Method for monitoring of a communication link between a source network node and a destination network node, comprising  
- employing, on said communication link, the IPSec protocol for tunneling IP packets between the source network node and the destination network node,  
- transmitting an acknowledgement packet by the destination network node if at least one of a first condition and a second condition is fulfilled, wherein said acknowledgement packet comprises at least the sequence number of the last received IPSec packet and at least one value corresponding to the amount of data received via the IPSec communication link,  
said first condition being the reception of at least a predetermined number of

12           IPSec packets after transmission of the previous acknowledgement packet, and  
13           said second condition being the reception of a packet via the communication link  
14           after a predetermined time has passed after transmission of the previous  
15           acknowledgement packet.

1           3. [original] A method according to claim 2, wherein said acknowledgement packet  
2           comprises at least a packet counter value indicating the number of packets received via  
3           the communication link.

1           4. [original] A method according to claim 2, wherein said acknowledgement packet  
2           comprises at least a byte counter value indicating the number of bytes received via the  
3           communication link.

1           5. [original] A method according to claim 2, wherein said acknowledgement packet  
2           comprises at least a packet counter value indicating the number of packets received via  
3           the communication link and a byte counter value indicating the number of bytes received  
4           via the communication link.

1           6. [original] A method according to claim 2, further comprising at least the step of  
2           determining the packet success rate of the communication link at least partly on the basis  
3           of information contained in an acknowledgement packet.

1           7. [original] A method according to claim 2, further comprising at least the step of  
2           determining the throughput of the communication link at least partly on the basis of  
3           information contained in an acknowledgement packet.

1 8. [currently amended] A method ~~according to claim 1, further comprising at least the~~  
2 steps of for monitoring of a communication link between a source network node and a  
3 destination network node, comprising

4 - employing, on said communication link, the IPSec protocol for tunneling IP  
5 packets between the source network node and the destination network node,

6 - transmitting an acknowledgement packet by the destination network  
7 node if at least one of a first condition and a second condition is fulfilled,

8 said first condition being the reception of at least a predetermined number  
9 of IPSec packets after transmission of the previous acknowledgement  
10 packet, and

11 said second condition being the reception of an IPSec packet via the  
12 communication link after a predetermined time has passed after  
13 transmission of the previous acknowledgement packet

14 - storing of the sequence number and the transmission time of each IPSec  
15 packet transmitted from the source network node to the destination network node  
16 in a memory means, and

17 - determining the round trip time of the communication link on the basis of  
18 the reception time of an acknowledgement packet and the stored transmission  
19 time of the corresponding transmitted packet.

1 9. [currently amended] Method for monitoring of a plurality of communication links  
2 between a source network site and a destination network site, each of the sites having  
3 at least one network node,  
4 in which method an active communication link is monitored and an inactive communication

link is monitored,  
said method comprising at least the following steps for monitoring an active communication link between the source network site and the destination network site, the active communication link employing the IPSec protocol:

the step of transmission of an acknowledgement packet by the destination network node if at least one of a first condition and a second condition is fulfilled, said first condition being the reception of at least a predetermined number of IPSec packets after transmission of the previous acknowledgement packet, and said second condition being the reception of a packet via the communication link after a predetermined time has passed after transmission of the previous acknowledgement packet,

and said method comprising at least the following steps for monitoring an inactive communication link between the source network site and the destination network site:

- transmitting a probe packet from a source node at the source network site via said inactive communication link to a destination node at the destination network site,
- storing the transmission time of said probe packet in a memory means,
- transmitting a response packet from said destination node to said source node as a response to receiving a probe packet,
- determining the round trip time of said inactive communication link from the difference of the reception time of the response packet and the stored transmission time of the corresponding probe packet
- maintaining present status of said active and inactive communications links or replacing said active communication link with said inactive communication

30            link based on results of said monitoring.

- 1            10. [original] A method according to claim 9, said method further comprising the steps of
- 2                            - transmitting a plurality of probe packets from said source node at the
- 3            source network site via said inactive communication link to said destination node
- 4            at the destination network site,
- 5                            - receiving response packets to said probe packets, and
- 6                            - determining the packet success rate of said inactive communication link
- 7            from the number of said received response packets and the number of
- 8            transmitted probe packets.

- 1            11. [currently amended] A network node ~~for communicating with the IPSec protocol with~~
- 2            ~~a second network node via a communication link, said network node~~ comprising at least
- 3                            - means for communicating over a IPSec protocol communication link with
- 4            a second network node using IPSec packets in order to tunnel IP packets
- 5            transmitted to said second network node,
- 6                            - means for sending acknowledgment packets for said IPSec packets
- 7            containing IP packets,
- 8                            - means for receiving said acknowledgement packets for said IPSec
- 9            packets ~~transmitted by the network node,~~
- 10                            - means for obtaining a sequence number of an IPSec packet from said a
- 11            received acknowledgement packet,
- 12                            - means for obtaining a value from said the acknowledgement packet, said
- 13            value corresponding to the amount of data received via the communication link by
- 14            said the second network node, and

15                               - means for determining the packet success rate of the communication link  
16                               at least partly on the basis of said value.

1       12. [original] A network node according to claim 11, further comprising at least means  
2       for determining the throughput of the communication link at least partly on the basis of  
3       said value.

1       13. [currently amended] A network node ~~according to claim 11, further comprising at~~  
2       least comprising at least

3                               - means for communicating over a IPSec protocol communication link with  
4                               a second network node in order to tunnel IP packets transmitted to said second  
5                               network node.

6                               - means for sending IPSec packets containing IP packets.

7                               - means for receiving acknowledgement packets for said IPSec packets.

8                               - means for obtaining a sequence number of an IPSec packet from a  
9                               received acknowledgement packet.

10                              - means for storing in a memory means the sequence number and the  
11                              transmission time of each IPSec packet transmitted by the network node via the  
12                              communication link, and

13                              - means for determining the round trip time of the communication link on the  
14                              basis of the reception time of an acknowledgement packet and the stored  
15                              transmission time of the corresponding transmitted packet.

1       14. [currently amended] A network node for communicating with the IPSec protocol with  
2       a second network node via a communication link, said network node comprising at least

3                   - means for communicating over a IPSec protocol communication link with  
 4                   a second network node in order to tunnel IP packets transmitted from said second  
 5                   network node.

6                   - means for sending IPSec packets containing IP packets.

7                   - means for transmission of transmitting an acknowledgement packet if at  
 8                   least one of a first condition and a second condition is fulfilled,

9                   said first condition being the reception of at least a predetermined number  
 10                  of IPSec packets after transmission of the previous acknowledgement  
 11                  packet, and

12                  said second condition being the reception of a packet via the  
 13                  communication link after a predetermined time has passed after  
 14                  transmission of the previous acknowledgement packet.

1           15. [currently amended] A network node ~~according to claim 14, said network node~~  
 2           ~~further~~ comprising at least

3                   - means for communicating over a IPSec protocol communication link with  
 4                   a second network node in order to tunnel IP packets transmitted from said second  
 5                   network node.

6                   - means receiving IPSec packets containing IP packets.

7                   - means transmitting an acknowledgement packet if at least one of a first  
 8                   condition and a second condition is fulfilled.

9                   - means for including inserting a sequence number of a received IPSec  
 10                  packet and at least one value corresponding to the amount of data received via  
 11                  the communication link in said acknowledgement packet,

12                  said first condition being the reception of at least a predetermined number of IPSec

13 packets after transmission of the previous acknowledgement packet, and  
14 said second condition being the reception of a packet via the communication link after a  
15 predetermined time has passed after transmission of the previous acknowledgement  
16 packet.

1 16. [currently amended] A network node according to claim 15, said network node  
2 further comprising at least means for including inserting a packet counter value in said  
3 acknowledgement packet, said packet counter value indicating the number of packets  
4 received via the communication link.

1 17. [currently amended] A network node according to claim 15, said network node  
2 further comprising at least means for including inserting a byte counter value in said  
3 acknowledgement packet, said byte counter value indicating the number of bytes  
4 received via the communication link.

1 18. [currently amended] A network node ~~for communicating with the IPSec protocol~~  
2 ~~with a second network node via a communication link, said network node comprising at~~  
3 ~~least~~

4 - means for communicating over a IPSec protocol communication link with  
5 a second network node in order to tunnel IP packets transmitted from said second  
6 network node.

7 - means for ~~transmission of~~ transmitting an acknowledgement packet if at  
8 least one of a first condition and a second condition is fulfilled,

9 said first condition being the reception of at least a predetermined number  
10 of IPSec packets after transmission of the previous acknowledgement



11 packet, and  
 12 said second condition being the reception of a packet via the  
 13 communication link after a predetermined time has passed after  
 14 transmission of the previous acknowledgement packet,  
 15 - means for sending IPSec packets.  
 16 - means for receiving acknowledgement packets for said IPSec packets  
 17 transmitted by the network node,  
 18 - means for obtaining a sequence number of an IPSec packet from a  
 19 received acknowledgement packet,  
 20 - means for obtaining a value from the acknowledgement packet, said  
 21 value corresponding to the amount of data received via the communication link by  
 22 the second network node, and  
 23 - means for determining the packet success rate of the communication link  
 24 at least partly on the basis of said value.

1 19. [currently amended] Software program product for a network node for  
 2 communicating with the IPSec protocol with a second network node via a communication  
 3 link, said software program product comprising at least  
 4 - software program code communicating over a IPSec protocol  
 5 communication link with a second network node in order to tunnel IP packets  
 6 transmitted from said second network node.  
 7 - software program code receiving IPSec packets containing IP packets.  
 8 - software program code means for transmission of transmitting an  
 9 acknowledgement packet if at least one of a first condition and a second  
 10 condition is fulfilled,

11                   said first condition being the reception of at least a predetermined number  
12                   of IPSec packets after transmission of the previous acknowledgement  
13                   packet, and  
14                   said second condition being the reception of a packet via the  
15                   communication link after a predetermined time has passed after  
16                   transmission of the previous acknowledgement packet,  
17                   - software program code means for receiving acknowledgement packets  
18                   for IPSec packets transmitted by the network node,  
19                   - software program code means for obtaining a sequence number of an  
20                   IPSec packet from a received acknowledgement packet,  
21                   - software program code means for obtaining a value from the  
22                   acknowledgement packet, said value corresponding to the amount of data  
23                   received via the communication link by the second network node, and  
24                   - software program code means for determining the packet success rate  
25                   of the communication link at least partly on the basis of said value.

1       20. [new] Software program product for a network node for communicating with the  
2       IPSec protocol with a second network node via a communication link, said software  
3       program product comprising at least  
4                   - software program code communicating over a IPSec protocol  
5       communication link with a second network node in order to tunnel IP packets  
6       transmitted to said second network node,  
7                   - software program code sending IPSec packets containing IP packets,  
8                   - software program code receiving acknowledgement packets for said  
9       IPSec packets,

- 10                   - software program code obtaining a sequence number of an IPSec  
11 packet from a received acknowledgement packet,  
12                   - software program code storing in a memory means the sequence  
13 number and the transmission time of each IPSec packet transmitted by the  
14 network node via the communication link, and  
15                   - software program code determining the round trip time of the  
16 communication link on the basis of the reception time of an acknowledgement  
17 packet and the stored transmission time of the corresponding transmitted packet.

- 1     21. [new] Method for monitoring of a communication link between a source network  
2 node and a destination network node, comprising  
3                   - employing, on said communication link, the IPSec protocol for tunneling IP  
4 packets of one or more TCP/IP connections between the source network node  
5 and the destination network node,  
6                   - transmitting, separately from TCP retransmission scheme carried out on  
7 said one or more TCP/IP connections, an acknowledgement packet by the  
8 destination network node if at least one of a first condition and a second condition  
9 is fulfilled,  
10                   said first condition being the reception of at least a predetermined number  
11 of IPSec packets after transmission of the previous acknowledgement  
12 packet, and  
13                   said second condition being the reception of an IPSec packet via the  
14 communication link after a predetermined time has passed after  
15 transmission of the previous acknowledgement packet.

- 1        22. [new] A method according to claim 21, comprising tunneling IP packets of two or  
2        more TCP/IP connections by means of said communication link using the IPSec protocol.